



EXPLANATION

- OVERBURDEN ISOPACHS - Showing thickness of overburden, in feet, from surface to top of coal bed. Dashed where vertical accuracy possibly not within 40 feet. Isopach interval 200 feet (61 m).
 - DRILL HOLE - Showing thickness of overburden, in feet, from surface to top of coal bed.
 - MINING-RATIO CONTOUR - Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas underlain by coal of Reserve Base thickness within the stripping-limit (in this quadrangle, the 200-foot-overburden isopach). To convert mining ratio to cubic meters of overburden per metric ton of recoverable coal, multiply mining ratio by 0.8428.
 - UGL[29] - Upper Coal Group, zone L, coal bed [29]
 - COAL BED SYMBOL AND NAME - Coal bed identified by bracketed numbers is not formally named, but is numbered for identification purposes in this quadrangle only.
 - TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Short dashed where projected by present authors.
 - TRACE OF FAULT - Bar and ball on down-thrown side when direction of movement is known. Dashed where inferred or approximately located.
- To convert feet to meters, multiply feet by 0.3048.

COAL RESOURCE OCCURRENCE MAP OF THE BREEZE MOUNTAIN QUADRANGLE,
ROUTT AND MOFFAT COUNTIES, COLORADO
BY
DAMES & MOORE
1979